

# SADOLIN Hardwood Oil

Unique product suitable for garden furniture and wooden decks with excellent absorption characteristics where the natural beauty of the wood is wanted.



**Enhances the natural beauty of the wood**  
**Easy to apply**  
**Excellent absorption characteristics**

**Product Description:** Sadolin Hardwood Oil is a premium high-quality hardwood oil developed to offer other benefits than those normally associated with traditional wood protection. Sadolin Hardwood Oil absorbs deeply into the surface of most timber species and provides protection against the weather. Sadolin Hardwood Oil is water repellent and is especially suitable for all exterior hardwood surfaces where a natural appearance is required.

Sadolin Hardwood Oil is recommended for wooden garden furniture and decks.

**Product Range:** 1. Colourless 3. Teak Natural

**Preparation:** Sadolin Hardwood Oil is recommended for use on bare timber, as well as timber surfaces which were previously coated with other oil treatments or timber coatings that do not provide a surface film build e.g. preservative pre-treatments. Ensure that the timber is clean, dry and free from grease. Timber species that contain high levels of natural oils or extractives (e.g. Teak, Iroko) should be thoroughly degreased, prior to treating with Sadolin Hardwood Oil.

Non-durable timbers located in exterior areas should receive a preservative pre-treatment of Sadolin Base prior to the application of Sadolin Hardwood Oil. Preservative pre-treatments must be fully dried before the application of Sadolin Hardwood Oil.

**Application:** Stir well before and during application and apply by brush or cloth. Do not apply at temperatures below 5°C. Do not thin.

Apply one coat of Sadolin Hardwood Oil and allow it to dry for 5 to 30 minutes depending on the temperature and humidity. Remove any residues of Sadolin Hardwood Oil, which have not been absorbed, by gently wiping with a cloth. This will help to prevent “glossy” blemishes on the surface.

For maximum durability, apply at least 2 coats of Sadolin Hardwood Oil. The colourless version is less durable than the coloured version. It is recommended that at least one coat of Sadolin Hardwood Oil is applied every year. For best results apply 3 coats.

**Coverage:** Approximately 15-18 m<sup>2</sup>/litre on planed wood.

**Drying Time:** Touch dry: 4-6 hours.  
Repainting: Subsequent coats can be applied after 12-24 hours.

**Cleaning:** Clean the brushes or rollers immediately after use in white spirit.

**Important Information:** Protect from frost.  
Shelf life: (Unopened) at least 5 years from production date.  
Please refer to the Technical Data Sheet for detailed information.



Rev. 1.0/01-02-01